



COMPANIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

BRAKE FLUID DOT – 4

GLOBAL RACING OIL BRAKE FLUID DOT-4 is a synthetic fluid for brake systems (disk or tambour), and gear commanders. It is especially recommended for its high boiling point, for tourism vehicles, motorcycles, trucks, buses, public works machinery, etc. It is characterized by:

- * EXCELLENT THERMAL STABILITY
- * IT GUARANTEES ADDITIONAL SAFETY
- * DRY BOILING POINT +265 °C
- * WET BOILING POINT + 185 °C
- * HIGH ANTI-WEAR, ANTI-OXIDANT AND ANTI-FOAMING POWER

Formulated with the most finest and exclusive synthetic bases, outperforming the requirements of manufacturers.

- * High performance fluid
- * Absolute safe working: immediate response to intensive use.
- * Absolutely compatible at any dilution with similar fluids

Density at 15 °C	1,050
Dry boiling point	260 °C
Wet boiling point	160 °C
Viscosity at -40°C	up to 1500 (típic 1.400 cSt)

According to the exigencies :

FM VSS 116 (DOT-4), SAE J1704, ISO 4925

REV: 05/17

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPANIA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

COMPANY CERTIFIED

